



PLASTOL ULTRA 209

HIGH RANGE WATER REDUCING ADMIXTURE

DESCRIPTION

PLASTOL ULTRA 209 high-range water-reducing and super plasticizing admixture is formulated using advanced polycarboxylate technology, specifically engineered for concrete to provide maximum water reduction, slump, flow, and improved finishing characteristics of concrete. In addition, PLASTOL ULTRA 209 provides high compressive strengths, flexural strength, and excellent setting characteristics. PLASTOL ULTRA 209 can be used to reduce the total cement content and used in combination with supplementary cementitious materials. PLASTOL ULTRA 209 does not contain added chlorides or chemicals known to promote the corrosion of steel.

PRIMARY APPLICATIONS

- Precast/pre-stressed concrete
- Self-Consolidating Concrete (SCC)
- High slump, flowable concrete
- Low water to cement ratio concrete
- High early strength concrete
- Ready-mix concrete
- Flatwork and mass concrete

FEATURES/BENEFITS

- Superior slump gain
- Consistent control of air content
- Improved cement hydration
- Low dosage
- Higher early and ultimate strengths
- Lowers number of rejected concrete loads
- Quicker stripping times
- Aids in concrete placement and reduces labor cost
- Improved finishability

TECHNICAL INFORMATION

| PROPERTY | VALUE |
|------------------|--------------------|
| Specific Gravity | 1.09 ± 0.02 @27°C |
| Physical State | Light brown liquid |
| Base Material | Polycarboxylate |
| pH | Minimum 6 |
| Chloride Content | <0.2 % |

Compatible with all cement types like OPC, OPC+Fly ash, PSC etc.,

PACKAGING

PLASTOL ULTRA 209 is packaged in 220 Kgs.

SHELF LIFE

1 Year in original, unopened container.

SPECIFICATIONS/COMPLIANCES

- Confirms the requirements of
- IS 9103/2007
- ASTM C 494, Type A,F
- AASHTO M 194

DIRECTIONS FOR USE

- Normal dosage range is 200 ml - 600 ml/50 kg of cement.
- However the optimum dosage is determined by site trials.
- PLASTOL ULTRA 209 should be added to initial batch water of the concrete mixture.
- Do not dispense on to dry cement.
- Over dosing leads to retardation of setting times of concrete, Mix may segregate and bleeding of concrete.

PRECAUTIONS/LIMITATIONS

- Care should be taken to maintain PLASTOL ULTRA 209 above freezing, however, freezing and subsequent thawing will not harm the material if thoroughly agitated.
- Do not agitate with air.
- Add to concrete mix independent of other admixtures.
- In all cases, refer the Safety Data Sheet before use.

June 24

(Plastol Ultra 209)

To the best of our knowledge the technical data contained herein are true and accurate at the date of issuance and are subject to change without prior notice. User must contact StonCor Middle East to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to StonCor Middle East Quality Control. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any, is limited to replacement of products. Prices and cost data, if shown, are subject to change without prior notice. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY STONCOR MIDDLE EAST, EXPRESS OR IMPLIED, STATUTORY BY OPERATION OF LAW OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.